



11019: 6" New Construction Shallow IC Airtight Housing

Specification Images:



Dimensions:

- Diameter:** 6 3/8"
- Length:** 13 1/2"
- Width:** 10 3/4"
- Height:** 6 1/8"
- Weight:** 2 lbs.

Features:

- Easily converts to LED with optional replacement lamps

Material List:

1 Housing - Steel - Raw Steel

Safety Listing:

Safety Listed for Damp Locations / IC  
Safety Listed for Damp Locations / IC

Instruction Sheets:

English (HC-958)

**Collection:** Recessed Lighting

New Construction Shallow IC Airtight Housing

Trims: 11037AT, 11020AT, 11033AT, 11034AT, 11035AT, 1136AT, 11055AT, 1158AT, 1159AT

Airtight Construction: Meets airtight requirements for 2.0 CFM or less air leakage.

Safe- Thermally Protected/Listed for Damp Location: IC housing is approved for use in direct contact with insulation.

Housing Adjustment: Housing adjusts vertically for various ceiling thicknesses.

Joist Tab: Tab to locate on bottom of joist.

Notch for T-Bar Ceilings: No clips required. Secure bar hanger to T-Bars with wires or screws.

Snap-In Socket: Snap in socket locates lamp in optimum position.

Sealed Trim: One piece sealed trims. No light leaks.

Bar Hanger: Break-away bar hangers easily extend and will not fall out of plaster flange, providing sturdy installation.

Bar Hanger Locking Screw: Tighten screw to lock bar hangers in place.

Quick Hit: Integral captive nails included and positioned for fast, easy installation.

Hinged Door: The hinged junction box door allows full access for wiring while remaining attached to the recess housing.

Junction Box with Integral Romex Connector: Junction box with integral romex connector, quick-push and lock connector and through circuit wiring with 4 in, 4 out #12 wire, saves installation time.

**UPC #:**785652110191

**Finish:** Not Applicable ( )

Shipping Information:

Package Type	Product #	Quantity	UPC	Length	Width	Height	Cube	Weight	Frt. Class	UPS Ship
Individual	11019	1	785652110191	14	11	7	0.624	2.4	100	Yes
Master Pack		6	10785652110198	25	20	7.25	2.098	18.1	100	Yes
NJ Pallet		240		48	40	72.25	80.278	724		No
NV Pallet		216		48	40	72.25	80.278	651.6		No

## Trim



11020AT-15  
**RECESSED TRIM**  
White Steel Trim  
Maximum Wattage:  
75w PAR30L  
65w BR30  
15w PAR30L  
15w BR30



11033AT-15  
**6" Flat Glass Shower Trim**  
Satin White Glass Diffuser  
White Aluminum Reflector  
White Aluminum Trim  
Maximum Wattage:  
40w A19  
8w A19  
Suitable For Shower Light



11034AT-15  
**RECESSED TRIM**  
Satin White Glass Diffuser  
White Aluminum Reflector  
White Aluminum Trim  
Maximum Wattage:  
40w A19  
8w A19  
Suitable For Shower Light



11035AT-15  
**RECESSED TRIM**  
Satin White Glass Diffuser  
White Aluminum Reflector  
White Steel Trim  
Maximum Wattage:  
40w A19  
8w A19



11037AT-15  
**6" Regressed Eyeball Trim**  
White  
White Steel Trim  
Maximum Wattage:  
75w PAR30L  
65w BR30  
15w PAR30L  
15w BR30



11055AT-15  
**6" Fresnal Glass Shower T**  
Clear Glass Lens  
White Aluminum Reflector  
White Aluminum Trim  
Maximum Wattage:  
40w A19  
8w A19  
Suitable For Shower Light



1136AT-15  
**6" Eyeball Trim**  
White  
White Steel Trim  
Maximum Wattage:  
75w PAR30L  
65w BR30  
15w PAR30L  
15w BR30



1158AT-14  
**6" Deep Cone Baffle Trim**  
White Trim / Baffle Aluminum Trim  
Maximum Wattage:  
50w PAR30S  
75w PAR30L  
65w BR30  
15w PAR30L  
15w BR30



1158AT-15  
**RECESSED TRIM**  
Black Aluminum Baffle  
White Aluminum Trim  
Maximum Wattage:  
50w PAR30S  
75w PAR30L  
65w BR30  
15w PAR30L  
15w BR30



1159AT-14  
**6" Shower Baffle Trim**  
White Trim / Baffle Aluminum Baffle  
White Trim / Baffle Aluminum Trim  
Maximum Wattage:  
50w PAR30S  
75w PAR30L  
13.5w A19  
15w PAR30L  
15w BR30  
Suitable For Shower Light