

1128: 6" New Construction IC Airtight Housing



Dimensions:

6 3/8" 13 1/2" Length: Width: 10 3/4" 7 7/8" Height:

Weight: 2.9 lbs.

Features:

· Easily converts to LED with optional replacement lamps

1 Housing - Steel / Aluminum - Raw Steel

Safety Listing:

Safety Listed for Damp Locations Safety Listed for Damp Locations

Instruction Sheets:

Bilingual (English - French) (HC-438FB)

Collection: Recessed Lighting

This IC recessed light housing features an air-tight application providing quality illumination while offering energy efficiency and lower operating costs

Housing Adjustment: Housing adjusts vertically for various ceiling

Airtight Construction: Meets airtight requirements for 2.0 CFM or less air leakage.

Joist Tab: Tab to locate on bottom of joist.

Notch for T-Bar Ceilings: No clips required. Secure bar hanger to T-Bars with wires or screws

Bar Hanger: Break-away bar hangers easily extend and will not fall out of plaster flange, providing sturdy installation.

Quick Hit: Integral captive nails included and positioned for fast, easy installation.

Hinged Door: The hinged junction box door allows full access for wiring while remaining attached to the recess housing

Bar Hanger Locking Screw: Tighten screw to lock bar hangers in place.

Junction Box with Integral Romex Connector: Junction box with integral romex connector, quick-push and lock connector and through circuit wiring with 4 in, 4 out #12 wire, saves installation time.

Safe- Thermally Protected/Listed for Damp Location: IC housing is approved for use in direct contact with insulation.

UPC #:785652112805

Finish: Not Applicable ()

Shipping Information:

11 0										
Package Type	Product #	Quantity	UPC	Length	Width	Height	Cube	Weight	Frt. Class	UPS Ship
Individual	1128	1	785652112805	14.3	9.3	8	0.616	3.15	100	Yes
Master Pack		6	10785652112802	25.6	19.2	8.7	2.475	22	100	Yes
NJ Pallet		168		48	40	76	84.444	616		No
NV Pallet		192		48	40	76	84.444	704		No

Trim









1120-15 6" Open Trim

White Steel Trim Maximum Wattage: 75w PAR30L 65w BR30 13.5w A19 15w PAR30L 15w PAR30L



White Trim / Baffle Aluminum Baffle White Trim / Baffle Aluminum Trim Maximum Wattage: 50w PAR30S 75w PAR30L 65w BR30

1126-14 6" Steel Baffle Trim

White Trim / Baffle Steel Baffle Maximum Wattage: 50w PAR30S 75w PAR30L 65w BR30

1126-15

RECESSED TRIM

Black Steel Baffle White Steel Trim Maximum Wattage: 50w PAR30S 75w PAR30L 65w BR30









1133AT-15

6" Flat Glass Shower Trim

White Glass Diffuser White Plastic Trim Maximum Wattage: 40w A19 8w A19 Suitable For Shower Light 1134-68

6" Drop Acrylic Shower Tr

White Plastic Plastic Diffuser White Plastic Trim Maximum Wattage: 40w A19 8w A19 Suitable For Shower Light

1135AT-15

RECESSED TRIM

Smooth White Glass Diffuser White Steel Trim Maximum Wattage: 40w A19

1136-15

6" Eyeball Trim

White White Steel Trim Maximum Wattage: 75w PAR30L 65w BR30 15w PAR30L 15w BR30









1136AT-15

6" Eyeball Trim

White White Steel Trim Maximum Wattage: 75w PAR30L 65w BR30 15w PAR30L 15w BR30

1151AT-14

6" Baffle Trim

White Trim / Baffle Aluminum Trim Maximum Wattage: 50w PAR30S 75w PAR30L 90w PAR38 65w BR30 13.5w A19 15w PAR30L 18w PAR38 15w BR30

1151AT-15

15w BR30

RECESSED TRIM

Black Aluminum Baffle White Aluminum Trim Maximum Wattage: 50w PAR30S 75w PAR30L 90w PAR38 65w BR30 13.5w A19 15w PAR30L 18w PAR38

1154AT-14

6" Open Cone Shower Trim

White Trim / Baffle Aluminum Baffle White Trim / Baffle Aluminum Trim Maximum Wattage: 50w PAR30S 75w PAR30L 90w PAR38 13.5w A19 15w PAR30L 18w PAR38 15w BR30 Suitable For Shower Light

Vist our web site at www.SeaGullLighting.com 1128 - page 3 of 3



1155AT-15 6" Fresnal Glass Shower T Clear Glass Lens White Aluminum Trim Maximum Wattage: 40w A19 8w A19 Suitable For Shower Light