

MOXY Chandelier
3-697-xx


oxygen

FIXTURE TYPE _____


LOCATION _____

PROJECT _____

DATE _____




-24 Satin Nickel



-40 Aged Brass

LIGHT SOURCE	LED Arrays, 3000K, CRI 90
LUMINAIRE POWER	33.4W at 120V
RATED LIFE	50000 hr RL
OPTIONAL COLOR TEMPERATURES	3000K Only
LUMEN OUTPUT	Delivered: 893 lm (LM-79)
INPUT VOLTAGE	120V AC, 60Hz
DRIVER OUTPUT	720mA, 30.2W max power
DIMMING	TRIAC Dimming
CONSTRUCTION	Cold Rolled Steel Housing and Canopy
DIFFUSER	- Clear Bubble Acrylic
FINISHES	Satin Nickel (-24), Aged Brass (-40)
MOUNTING	4" Octagonal J-Box
STANDARDS	ETL Damp listed, Conforms to UL STD 1598, Certified CAN/CSA STD C22.2 No 250.0.



DIMENSIONS

Dia. Canopy: 6.69"

W. Fixture: 32.00"

H. Fixture: 27.00"

Supplied with 2-8", 2-12", and 3-16" stems to customize hanging height

Note: Canopy swivel allows up to a 22° slope

Order example for standard fixture:
3-697-24 (x- Voltage - xxx-Sequence # - xx-Finish)
3: 120V Only

