DICE - model: FM-40

dweLED™ Ceiling Flush Mounts

WAC LIGHTING

Responsible Lighting®



PRODUCT DESCRIPTION

Thick-walled glass is uniformly illuminated in a design made for LED technology in a rectangular format. Full range dimming control. Mounts as robust ceiling luminaire or a compelling wall sconce.

FEATURES

- Etched ¾" thick pressed glass diffuser with interior ceramic glaze
- · Mount as a ceiling fixture or wall sconce
- · ADA compliant when mounted on wall
- ETL & cETL damp location listed
- 100%-10% electronic low voltage (ELV) dimming see specification sheet for list of tested dimmers
- Also rated for installation in closets
- Transformer located in J box
- 277V available (special order)
- CRI: 90
- 45,000 hour rated life
- 5 year warranty

SPECI	EIC	ATI	$^{\circ}$	ıc
SPECI	ידוכ	AH	UI	VЗ

Construction: Durable die-cast aluminum canopy, with thick opal glass.

Light Source: LED

Dimming: 100%-10% Electronic Low Voltage (ELV)

 $\textbf{Standards:} \ \mathsf{ETL} \ \& \ \mathsf{cETL} \ \mathsf{damp} \ \mathsf{location} \ \mathsf{listed}, \ \mathsf{ADA} \ \mathsf{compliant}$

				LED	Delivered			
		Color Temp	Watt	Lumens	Lumens	Finish		
14"25%" []i] 5%"	FM-4014-27 FM-4014-30	2700K 3000K	31W 31W	1323 1356	610 640	BN	Brushed Nickel	-
6", 2%"	FM-4006-27 FM-4006-30	2700K 3000K	17.5W 17.5W	779 800	355 365			
9", 23/4"	FM-4009-27 FM-4009-30	2700K 3000K	27W 27W	1341 1376	885 910	BN BZ CH	Brushed Nickel Bronze Chrome	
12" 25%"	FM-4012-27 FM-4012-30	2700K 3000K	25W 25W	1990 2200	890 985			

Example: FM-4014-27-BN

FM-40

For 277V, add an "F" before the color temperature: FM-4014F-27-BN

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050

Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760