


# CERVANTES 56" Ceiling Fan

FR-W1806-56L

## MODERN FORMS SMART FANS



### PRODUCT DESCRIPTION

Modern luxury is all about making life simpler- that's exactly what Cervantes does for you. With our Modern Forms app, you can map out schedules, optimize energy use and integrate with smart home devices you already own, like Amazon Alexa and Google Assistant. And Cervantes's clean, offset blades slice through the air with barely a whisper- that's because the powerful DC motor keeps things running smooth and super quiet. Available in versatile oil-rubbed bronze and graphite finishes.

### SPECIFICATIONS

- Construction:** Aluminum
- Blade:** 14° Pitch, 56" sweep, ABS
- Downrod:** 1" O.D. x 4.5"H included
- Mounting Slope:** Up to 30°
- Lead Wire:** 80"
- Hanging Weight:** 20 lbs
- Total Power:** 48.5W
- Standards:** ETL/cETL Wet Location listed

### FEATURES

- 6 fan speeds through both Summer and Winter Modes
- Silent DC motor
- Optional LED light kit included
- Includes RF wall control
- Additional RF wall control for 3, 4-way control sold separately
- Compatible with Modern Forms app

### LIGHT KIT PERFORMANCE

- Light Source:** LED
- Light Wattage:** 19.5W
- Dimming:** Integrated
- Color Temperature:** 3000K
- Rated Life:** 50,000 Hours
- Standards:** Title 24 JA8-2016 compliant

### ESTIMATED AIR PERFORMANCE

- Airflow:** 6577 cubic ft per minute on high
- Power:** 29 watts on high
- Airflow Efficiency:** 228 cubic ft per minute per watt
- Revolutions Per Minute:** 153 RPMs on high/98 RPMs on average

### WIRELESS PERFORMANCE


- RF Pairing Distance:** Up to 30 ft from fan
- Wi-Fi Range:** Up to 150 ft\*

### ORDER NUMBER

Model	LED Lumens	Delivered Lumens	Housing	Blade
FR-W1806-56L	1600	429	<b>GH</b> Graphite	<b>DW</b> Dark Walnut
			<b>OB</b> Oil Rubbed Bronze	<b>WG</b> Weathered Gray

Example: **FR-W1806-56L-GH/DW**

\*Results may vary based on application and surroundings.








modernforms.com  
Phone (866) 810.6615  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760

**OPTIONAL ACCESSORIES**

	<b>F-WC</b>	<b>WT</b> White	Control fan speed, light brightness and switch between Summer and Winter Modes from up to 30 ft away. One RF Wall control comes standard with each Modern Forms Smart fan.
	<b>F-TS</b>	<b>BK</b> Black <b>WT</b> White	Sold separately. Android tablet comes pre-loaded with Modern Forms app, Wi-Fi range up to 150 ft from router. Results may vary based on application/surroundings.
	<b>XF-12</b> 12in <b>XF-18</b> 18in <b>XF-24</b> 24in <b>XF-36</b> 36in <b>XF-48</b> 48in <b>XF-60</b> 60in <b>XF-72</b> 72in	<b>AS</b> Automotive Silver <b>BZ</b> Bronze <b>CFI</b> Carbon Fiber** <b>DW</b> Dark Walnut <b>GB</b> Gloss Black <b>GH</b> Graphite <b>GW</b> Gloss White <b>MB</b> Matte Black <b>MW</b> Matte White <b>OB</b> Oil Rubbed Bronze <b>SS</b> Stainless Steel <b>TT</b> Titanium Silver	All our downrods are 1" O.D. and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field.
	<b>XF-I</b>		Connects two downrods together.
	<b>XF-SCK</b>		Designed to accommodate buildings with steeper sloped ceilings up to 45° or 12/12 pitch.

Examples: RF Wall Control - **F-WC-WT**, Wi-Fi Touch Panel - **F-TS-WT**, Downrod - **XF-12-BZ**, Downrod Coupler - **XF-I-BZ**, Sloped Ceiling Kit - **XF-SCK-DW**

**NOTE:** Recommended maximum downrod length of 72" with 80" lead wire.

\*\*Carbon Fiber downrods available in 12", 18", 24" and 36"

**SUGGESTED DOWNROD HEIGHT USAGE**

Ceiling Height	15'	14'	13'	12'	11'	10'	9'
Downrod	72"	60"	48"	36"	24"	18"	12"

**SLOPED CEILING DEGREE CONVERSION CHART**

Degree	4-8°	9-13°	14-17°	18-21°	22-25°	26-29°	30-32°	33-35°	36-38°	39-41°	42-44°	45°
Ceiling Slope Pitch	1/12 pitch	2/12 pitch	3/12 pitch	4/12 pitch	5/12 pitch	6/12 pitch	7/12 pitch	8/12 pitch	9/12 pitch	10/12 pitch	11/12 pitch	12/12 pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45°.