

One-Light Pendant

 Ceiling chain or stem mounted • Damp location listed **PROGRESS LED**


Description:

The Fresnel one-light LED pendant has an antique-inspired Fresnel glass lens, industrial roots in form and function. 3000k, 90+ CRI 1,211 lumens.

Specifications:

- Brushed Nickel (-09) (Plated)
- Steel Construction
- Clear Fresnel glass lens
- Antique inspired with industrial roots
- 1,211 lumens 71.2 lumens/watt
- 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 10 feet of wire supplied
- Two 6", one 12", two 15" lengths of stem included
- Six links of 9 gauge chain supplied
- ENERGY STAR® qualified

Performance:

Number of Modules	1
Input Power	17w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	1211/71.2 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	60,000 (L70/TM-21)
FCC	Meets FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cCSAus Damp location listed ENERGY STAR® qualified

P5188-0930K9

Images:



Dimensions:

Diameter: 12-1/8"
 Height: 10-1/2"
 Overall Ht. W/Stem: 76-1/2"



P5188-0930K9

Dimming Notes:

P5188 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron	Nova T	NTELV-300
Lutron	Vierti	VTELV-600
Lutron	Maestro	MAELV-600
Lutron	spacer/system	SPSELV-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.