

ENDORSE

Wall mounted • Wet location listed



P6056-3130K9

Description:

Endorse celebrates the traditional form of a gas-powered coach light with illumination from an LED source. A die-cast aluminum, powdered coated frame created an intriguing visual effect with the clear beveled glass. An optional fluted glass column is offered as an accessory (P8774-31). 3000K, 90+ CRI, 623 lumens.

Specifications:

Black (-31) (powdercoat)
 Die-cast aluminum construction
 Clear glass beveled panels, Clear beveled panels glass
 Dimmable (See Dimming Notes)
 Back plate covers a standard 4" hexagonal recessed outlet box
 Mounting strap for outlet box included
 6" of wire supplied
 ENERGY STAR® qualified

Performance:

Number of Modules	1
Input Power	9w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	623/69.2 (LM-79)
CCT	3000 K
CRI	90
Life (hours)	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cCSAus Wet location listed ENERGY STAR® qualified

Images:



Dimensions:

Width: 6-3/4"
 Height: 12"
 Depth: 7-5/8"
 H/CTR: 3-1/4" (facing up)

P6056-3130K9

Dimming Notes:

P6056-3130K9 is designed to be compatible with many Electronic Low Voltage (ELV/Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron Diva DVELV-300P

Lutron Nova T NTELV-300

Lutron Vienti VTELV-600

Lutron Ariadni AYCL-153P

Lutron Diva DVCL-153P

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.