



▲ Designate proper finish suffix

Delta Faucet Company reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability.



see what Delta can do

# HAND SHOWER W/WALL MOUNT

■ Single-Setting Hand Shower

## **FEATURES:**

• Touch-Clean® Spray Holes

### **STANDARD SPECIFICATIONS:**

- Max. flow rate 1.75 qpm @ 80 psi, 6.6 L/min @ 550 kPa
- Certified dual check valves for backflow protection
- Hand held shower single spray setting
- 60"-82" (1524 mm 2083 mm) stretchable metal hose
- Wall mount for hands-free showering
- Single setting include: Full Body spray

### **WARRANTY:**

- Parts and Finish Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.).
- Please go to www.deltafaucet.com for the complete details of our limited warranty.



# **COMPLIES WITH:**

- ASME A112.18.1 / CSA B125.1◆
- ASME A112.18.3◆
- EPA WaterSense®
- ◆ Your Delta hand shower incorporates a backflow protection system that has been tested to be in compliance with ASME A112.18.3 and ASME A112.18.1/ CSA B125.1. It incorporates two certified check valves in series, which operate independently and are integral, non-serviceable parts of the wand assembly.

55 E. 111th Street, Carmel, IN 46280 350 South Edgeware Road, St. Thomas, ON N5P 4L1 © 2025 Delta Faucet Company