

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Line 48" Pendant

Model & Size	Color Temp & CRI	Watt	LED Lumens	Delivered Lumens	Finish
PD-51148 48"	2700K 90	48W	4017	2770	AL Brushed Aluminum
	3000K 90	48W	4435	3055	BK Black

Example: **PD-51148-27-AL**

- For 277V special order, add an "F" before the finish: PD-51148F-27-AL

DESCRIPTION

Like other Line family products, the Line chandelier features a super thin, edge-lit LED panel that provides ambient light. This dramatically proportioned luminaire offers a direct-indirect light distribution which delivers ample light to work surfaces free of shadows while also illuminating the ceiling and upper portion of walls to give the space the sense of immensity. A perfect addition to commercial offices or modern kitchen islands.

FEATURES


- Super thin, edge-lit LED panel illuminates up and down
- Integral swivel for sloped ceilings
- Six 12 inch and two 6 inch rods included (additional extension rods available)
- Transformer installed within the Junction Box, transformer dimension: 2.00" x 1.38" x 1.02"
- 5 year warranty

SPECIFICATIONS

Color Temp:	2700K, 3000K
Input:	120 VAC, 50/60Hz
CRI:	90
Dimming:	ELV: 100 - 10%, ELV: 100-10%
Rated Life:	80000 Hours
Mounting:	Heavy gauge retention clips support trim firmly. Safety cabling standard.
Standards:	ETL, cETL Damp Location Listed
Construction:	Aluminum hardware with ultra-thin light-guide acrylic diffuser



FINISHES



LINE DRAWING

