


- | | |
|--|---|
| R89-1TBOSCBG Finish(BG) <input type="checkbox"/> | LG89-7TBOSCBG Finish(BG) <input type="checkbox"/> |
| R89-1TBOSCC Finish(C) <input type="checkbox"/> | LG89-7TBOSCC Finish(C) <input type="checkbox"/> |
| R89-1TBOSCD Finish(D) <input type="checkbox"/> | LG89-7TBOSCD Finish(D) <input type="checkbox"/> |
| R89-1TBOSCK Finish(K) <input type="checkbox"/> | LG89-7TBOSCK Finish(K) <input type="checkbox"/> |
| R89-1TBOSCSDB Finish(SDB) <input type="checkbox"/> | LG89-7TBOSCSDB Finish(SDB) <input type="checkbox"/> |



Specifications

Features

- 1.8 GPM Flow Rate (Showerhead)
- All Metal Construction
- SecurePfit™ with Anti Handle Wobble
- Brass Ball Joint
- Requires OX8/JX8 Valve (Sold Separately)
- Valve Trim Only (1TBOSC Only)
- Shower Only (7TBOSC Only)
- Trim Only, Valve Not Included
- Easy To Clean Nozzles
- Limited Lifetime Warranty

- SecurePfit™
- Trim Only, Valve Not Included

Code Compliance

Pfister products are designed and manufactured in compliance with the following standards and codes:

- IAPMO Certified to ASME A112.18.1/CSA B125.1
- EPA WaterSense Certified
- CEC Certified/CALGreen compliant



Dimensions

