



- | | |
|--|---|
| R89-1TNTSLBG Finish(BG) <input type="checkbox"/> | LG89-7TNTSLBG Finish(BG) <input type="checkbox"/> |
| R89-1TNTSLC Finish(C) <input type="checkbox"/> | LG89-7TNTSLC Finish(C) <input type="checkbox"/> |
| R89-1TNTSLD Finish(D) <input type="checkbox"/> | LG89-7TNTSLD Finish(D) <input type="checkbox"/> |
| R89-1TNTSLK Finish(K) <input type="checkbox"/> | LG89-7TNTSLK Finish(K) <input type="checkbox"/> |
| R89-1TNTSLSDB Finish(SDB) <input type="checkbox"/> | LG89-7TNTSLSDB Finish(SDB) <input type="checkbox"/> |

Specifications

- SecurePfit™
- Trim Only, Valve Not Included

Features

- 1.8 GPM Flow Rate (Showerhead)
- All Metal Construction
- Brass Ball Joint
- SecurePfit™ with Anti-Handle Wobble
- Trim Only, Valve Not Included
- Easy to Clean Nozzles
- Optional Crosshandle Available, Order HHL-089-TNTSC* Separately
- Hold/Cold Indicator
- Metal Lever Handle
- Requires OX8/JX8 Valve (Sold Separately)
- Valve Trim Only (1TNTSL Only)
- Shower Only (7TNTSL Only)
- Limited Lifetime Warranty

Code Compliance

Pfister products are designed and manufactured in compliance with the following standards and codes:

- IAPMO Certified to ASME A112.18.1/CSA B125.1
- EPA WaterSense Certified
- CEC Certified/CALGreen compliant
- ADA Compliant - ANSI A117.1 (Lever Handles Only)



Dimensions

